



BID-0025
July, 1998

DMS-100™ Terminal-to-Network Interface
For Megalink™
ISDN Primary Rate Interface (PRI)

This document may not be reproduced without the express permission of Bell Canada
Any reproduction, without authorization, is an infringement of Bell Canada's copyright.

Copyright ©
Bell Canada
1998
All Rights Reserved

TABLE OF CONTENTS

	<u>Page</u>
DOCUMENT HISTORY	1
DISCLAIMER	2
1.0 SERVICE DESCRIPTION	3
2.0 SERVICE PROVISIONING	5
3.0 INTERFACE DESCRIPTION	6
3.1 Introduction	6
3.2 Physical Layer.....	6
3.3 Data Link Layer.....	6
3.4 Call Control Signaling.....	6
3.4.1 Bearer Service.....	7
3.4.2 Basic Call Services.....	7
3.4.3 Protocol and Procedures	8
3.5 Supplementary Services.....	9
3.5.1 Backup D-Channel.....	9
3.5.2 Called Number Delivery.....	9
3.5.3 Calling Number Delivery	9
3.5.4 Integrated Services Access (ISA)	11
3.5.5 Equal Access.....	12
3.5.6 Network Redirection and Reason	12
3.5.7 Special Number Services.....	13
3.5.8 Network Name.....	13
3.5.9 Release Link Trunk (RLT).....	13
APPENDIX A - Glossary	14

DOCUMENT HISTORY

-
- | | | |
|---|--------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | October 1997 | Initial issue
This issue replaces Stentor Interface Document ID-0005 issued on behalf of Bell Canada. |
| 2 | July 1998 | Revised to include additional feature functionality and to update Interface Specification from NIS A211-1 Release 6 to NIS A211-1 Release 7.05 |
-

RENAMED AS BELL CANADA BID-0025 FROM STENTOR ID-0030

DISCLAIMER

Bell Canada reserves the right to modify the interface described in this document for any reason including, but not limited to, ensuring that it conforms with standards promulgated by various agencies from time to time, utilization of advances in the state of the technical arts, or the reflection of changes in the design of any equipment, techniques or procedures described or referred to herein.

BELL CANADA SHALL NOT BE LIABLE FOR ANY DAMAGES OR INJURIES INCURRED BY ANY LEGAL PERSON OR PERSONS, INCLUDING BUT NOT LIMITED TO CORPORATIONS, ARISING DIRECTLY OR INDIRECTLY FROM A DESIGN INCOMPATIBILITY WITH THE NETWORK, OR ANY CAUSE WHATSOEVER.

Readers are specially advised that the technical requirements contained herein may change.

If further information is required, please contact:

BELL CANADA

Director - Interface Standards Research
Suite 640
160 Elgin Street
Ottawa, Ontario
K1G 3J4

In Canada:	1-877-77-TELCO (83526)
Worldwide:	613-781-7393
Fax:	613-781-1658
E-mail:	disclosure@bell.cdn-telco.com
Web-site:	bell.cdn-telco.com

1.0 SERVICE DESCRIPTION

This specification describes Megalink™, the Bell Canada ISDN Primary Rate Interface (ISDN PRI). Megalink™ is based on the Northern Telecom DMS-100™ Central Office switch. The interface requirements are defined in relevant portions of the Nortel publication, NIS A211-1, Release 7.05, "ISDN Primary Rate User - Network Interface Specification", except where amended by this document.

This publication may be obtained from:

BELL CANADA

Director - Interface Standards Research
Suite 640
160 Elgin Street
Ottawa, Ontario
K1G 3J4

In Canada:	1-877-77-TELCO (83526)
Worldwide:	613-781-7393
Fax:	613-781-1658
E-mail:	disclosure@bell.cdn-telco.com
Web-site:	bell.cdn-telco.com

This Northern Telecom publication was developed to include markets in addition to Bell Canada, and thus contains information which may not be applicable to Bell Canada's Megalink™ service.

All Bell Canada DMS-100™ switches will operate with at least Batch Change Supplement (BCS) 36 software level. Optional features Release Link Trunk and Calling Party Screening are only available when the DMS-100™ switch is at an NA007 level or above.

This document further clarifies basic call services and supplementary services which are defined in NIS A211-1, Release 7.05. The supplementary services as listed in NIS A211-1, Release 7.05 that will be offered by Bell Canada are:

- Backup D-Channel
- Called Number Delivery
- Calling Number Delivery
- Integrated Service Access
- Network Redirection and Reason
- Special Number Services
- Network Name
- Equal Access
- Release Link Trunk

2.0 SERVICE PROVISIONING

All PRIs provided by Bell Canada will be provided in a Call-by-Call service configuration. That is, with the exception of the D-channel, any DS-0/time slot may be used at any time to carry calls of any of the services subscribed to by the customer.

For basic call services, each B channel is switched independently by the network. Permanently connected B-Channels for dedicated access to link services are not supported.

In a single PRI configuration, the D-channel is assigned to time slot 24. The interface is configured as a "23 B + D" interface: up to 23 B channels and one D channel, providing for a combined total of up to 1.536 Mbps of user information in each direction.

Multiple PRI configurations may be implemented using either Facility Associated Signalling or Non-Facility Associated Signalling. If Facility Associated Signalling is used, a D channel is assigned to time slot 24 within each access DS-1. If Non-Facility Associated Signalling is used, a single D-channel may carry the signalling traffic for up to 20 PRI DS-1s, subject to the availability of sufficient access and switch port facilities. Further, if Non-Facility Associated Signalling is used, one time slot on one other DS-1 may be assigned for use as a backup D channel.

On DS-1's which do not contain a primary or backup D channel, all 24 time slots may be used to carry calls. This is only applicable to Non-Facility Associated Signalling.

3.0 INTERFACE DESCRIPTION

3.1 Introduction

NIS A211-1, Release 7.05, Section 1 applies at the ISDN PRI, with the following clarifications:

1. Services supported by Bell Canada are those listed in Section 1.0 of this document.
2. Section 4 of NIS A211, Release 7.05 and Section 2.4 of this document should be referenced with regard to Bearer Services.

This technical interface specification is arranged, for disclosure purposes, in the same general format as in NIS A211-1, Release 7.05.

3.2 Physical Layer

Section 2 of the NIS A211-1, Release 7.05 specification defines the physical layer (Layer 1) of the DMS-100™ Integrated Services Digital Network (ISDN) Primary Rate Interface (PRI) with the following clarifications.

1. The point of connection to the ISDN PRI is the Service Interface Jack (SIJ), which is provided by Bell Canada. The point of connection is a 15-pin DS-1 Digital Interface connector (CA81A) with pin assignments as described in CS-03. Optionally, if a standalone SIJ has been provided, the point of connection may be an 8 pin jack (CA48C) with pin assignments as described in CS-03 Part III.
2. Megalink™ will only support the Extended Superframe Format (ESF) and the B8ZS line code. In addition, the network supports CRC-6 messages, Facility Data Link (FDL) alarms, and performance messages (as described in paragraph 6.4 of NIS A211-1 Release 7.05 Chapter 2-6).
3. The option to support conventional bit robbing signaling trunks with A/B/C/D bit signaling or A/B bit signaling is not supported.

3.3 Data Link Layer

The data link layer is as specified in NIS A211-1, Release 7.05, Section 3.

3.4 Call Control Signaling

Section 4 of the NIS A211-1, Release 7.05 specification defines the call signaling protocol for DMS-100™ to CPE applications using an Integrated Services Digital Network (ISDN) Primary Rate Interface (PRI).

3.4.1 Bearer Service

Megalink™ supports the following bearer services:

- Speech
- 3.1 kHz audio
- 64 kbps unrestricted digital, rate adapted from 56 kbps
- 64 kbps clear unrestricted digital, circuit mode
- 64 kbps restricted, circuit mode

The above bearer services are specified in NIS A211-1, Release 7.05, with the following clarifications:

1. "Speech" and "3.1 kHz audio" bearer service requests in Bell Canada will be treated identically and calls with these bearer service requests will be routed over the regular PSTN (Public Switched Telephone Network). That is, end-to-end digital connectivity will not be assured.
2. In Bell Canada, a "64 kbps restricted" bearer service request shall be treated the same as a "64 kbps clear unrestricted digital" bearer service request.
3. The "64 kbps clear unrestricted digital" bearer service request shall ensure and guarantee end-to-end digital connectivity. If suitable digital facilities are not available, the call will be rejected with an appropriate cause value.

3.4.2 Basic Call Services

The basic call services are as specified in Section 4 of NIS A211-1, Release 7.05, with the following clarifications:

1. Routing of PRI calls is based on the dialed digits and the bearer capability. At this time no screening of bearer capability is performed by the network, all calls are presented to the PRI.
2. The ISDN PRI services provided are circuit-switched. The "dedicated" or "nailed-up" B channel, described in NIS A211-1, Release 7.05, Section 1, is not available.
3. Any call originating in the network which has evoked T-Link™ rate adaptation (Centrex III Data service) will be coded by the DMS-100™ as V.110 rate adaptation in the Bearer Capability IE Octet 5 in the SETUP message when presented to the Megalink™ Terminal equipment.

3.4.3 Protocol and Procedures

The protocol and procedures for the ISDN PRI are as specified in NIS A211-1, Release 7.05, Section 4, with the following clarifications:

1. The Notify message, described in Chapter 4-3 paragraph 3.1.6, is part of the Network Redirection and Reason service.
2. The Facility and Facility Reject messages described in Chapter 4-3 paragraph 3.3.1 and 3.3.2 and the Facility Information Element described in Chapter 4-4 paragraph 4.5.15 are part of the Release Link Trunk service.
3. The Calling Party Number information element, described in Chapter 4-4 paragraph 4.5.8, applies to the Calling Number Delivery service.
4. The Connected Number information element, described in Chapter 4-4 paragraph 4.5.12, applies to the Network Redirection and Reason service.
5. The Information Request information element, described in Chapter 4-4 paragraph 4.5.16, applies to the Network Redirection and Reason service.
6. The Network Specific Facilities information element, described in Chapter 4-4 paragraph 4.5.17, applies to the ISA service.
7. The Original Called Number and Redirection Number information elements, described in Chapter 4-4 paragraph 4.5.21 and 4.5.24, apply to the Network Redirection and Reason service.
8. Information elements used exclusively in supplementary services not supported by Bell Canada will be ignored.
9. Symmetric Call Control, as described in Annex D of Section 4, is not supported by Bell Canada.
10. The Display information element is not supported by Bell Canada in a NOTIFY message as described in Chapter 4-3 paragraph 3.1.6 since Connected Name Display is not supported.

3.5 Supplementary Services

This section defines the supplementary service capabilities which are being offered by Bell Canada, or which may be offered based on a customer request.

NIS A211-1, Release 7.05, Section 5 applies to ISDN PRI with the following clarifications.

3.5.1 Backup D-Channel

The Backup D-Channel service is associated only with non-facility associated signaling, that is, where a single D-channel is used to provide call control signaling for more than one DS-1 interface. This service provides a procedure for employing a standby D channel which is used if the primary D channel fails. All active calls are maintained during the switch-over to the D-channel. The Backup D-Channel service is available as an option.

An overview of backup D-channel service is provided in Section 5 of NIS A211-1, Release 6. The detailed protocol and procedures for this service are in Section 4 of NIS A211-1, Release 7.05.

3.5.2 Called Number Delivery

If a called user subscribes to this service, the Called party number information element is included in the SETUP message on each terminating call.

If the called user does not subscribe to this service the terminating SETUP message does not contain the Called party number information element.

This service is specified in Section 5 of NIS A211-1, Release 7.05.

3.5.3 Calling Number Delivery

The Calling Number Delivery service provides the directory number of the calling party to the PRI and from the PRI.

When the Calling Number Delivery (CND) service is active, the information element containing the calling party number will be delivered in the SETUP message unless the calling party number is not available. The number is not available when a call is routed over certain existing signaling systems (e.g., MF). If a call encounters this routing, the Calling party number information element is sent with the presentation indicator set to "number not available due to interworking". If the calling party has requested that the number not be displayed, the Calling party number information element will be delivered with no digits and the presentation indicator set to "presentation restricted".

If the PRI delivers a calling party number in the SETUP message with a presentation indicator (PI) of unrestricted, the network will forward the digit string to the terminator (assuming no interworking). Optionally the PRI may be configured such that the calling party number is always suppressed with a presentation indicator of restricted for a specific type of call.

While not currently a general offering, an option exists to screen and edit the calling party number in software loads NA007 and higher.

This service is specified in Section 5 of NIS A211-1, Release 7.05.

3.5.4 Integrated Services Access (ISA)

Integrated Services Access (ISA) permits a PRI to replace several dedicated trunk groups, resulting in efficiencies and simplified administration. ISA provides the capability to signal information which indicates the specific trunk type needed to complete a call, or from which a call is incoming. While dedicated facilities continue to exist in the network for INWATS, OUTWATS, TIE, PRIVATE and FX calls, a single PRI allows access to all of these facilities. ISA handles both incoming and outgoing calls on a PRI. This service is visible only to a telecommunications administrator, and does not affect end users.

This service is specified in Section 5 of NIS A211-1, Release 7.05, with the following clarifications:

1. Substitute "OUTWATS" with "WATS".
2. Substitute "INWATS" with "Toll free Service" or "800 Service".
3. Service Selector FX may be used to indicate incoming PSTN calls when a SID is required.
4. The ISA service, as offered by Bell Canada, will only allow the combinations of Numbering Plan Identification (NPI - in the Called party number information element) and Binary Facilities Coding Value (BFCV - in the Network specific facilities information element) as shown in the following table. All other combinations will cause the call to be rejected. The combination chosen determines whether "normal" (public network) or "customer specific" translations will be used.

<u>NPI</u>	<u>BFCV</u>	<u>Translation</u>
E.164	-	normal
Private	-	customer specific
E.164	INWATS	normal
E.164	OUTWATS	normal
Private	OUTWATS	customer specific
Private	PRIVATE	customer specific
Private	TIE	customer specific
E.164	FX	normal

5. A Public' calltype or service can only be specified by the absence of the NSF information element and an NPI of E.164. A BFCV of Public' is not supported in either direction. Therefore, a Service Identifier is not supported for a Public' call

3.5.5 Equal Access

The Equal Access feature provides PRI users with equal access to carrier networks (for example, IEC networks) for public network calls. The preferred carrier may be specified on a per call basis in either the dialed digits of the Called Party Number Information Element (for example 10XXX+ or 101XXXX) or by including a Transit Network Selection Information Element in the Setup message.

If the preferred carrier is not specified on a per call basis, a default carrier is selected by the network. The default carrier is selectable for each Megalink™ System Group.

This functionality is specified in Section 5 of NIS A211-1, Release 7.05.

3.5.6 Network Redirection and Reason

This service informs the calling and called parties about any redirection that may occur during the life of a call. Redirection may occur because of, for example, call forwarding or call transfer.

The redirection network service has three main features:

1. Notification of Redirection before answer: The calling party will be informed of the reason for redirection and the directory number of the new destination by means of the Redirection number information element in the NOTIFY message. Ex: call forward and call pickup.
2. Notification of Redirection after answer: The calling party will be informed of the reason for redirection by means of the Redirection Number information element in a Notify message and the directory numbers of the newly connected parties will be exchanged by means of the Connected Number information element in subsequent NOTIFY messages. Ex: call transfer.
3. Notification of Redirected Call: The new destination of a redirected call will be informed of the original destination and the reason for redirection by means of the Original called number information element, delivered in the SETUP message.

The following redirection services are supported:

- Call Forwarding Universal
- Call Forwarding Busy
- Call Forwarding No Answer
- Call Transfer
- Call Pickup

This service is specified in Section 5 of NIS A211-1, Release 7.05.

3.5.7 Special Number Services

Special Number Services enable access to certain Bell Canada services which are specified by dialed digits that do not necessarily conform to E.164, the ISDN/telephony numbering plan. Examples of these services include:

- 0
- 411
- 611
- 911

Not all of the above services are available in all areas, and some areas may have access to additional services.

This service is specified in Section 5 of NIS A211-1, Release 7.05.

3.5.8 Network Name

Network Name service allows the transport of Calling and Redirecting Names across PRI using the Setup Method. This allows an originating node to deliver the originator's name to the terminating node. Connected Party Name is not delivered by the network on redirected or on non-redirectioned calls.

This service is specified in Section 5 of NIS A211-1, Release 7.05.

3.5.9 Release Link Trunk (RLT)

The Release Link Trunk (RLT) feature will provide PRI trunk optimization software which will allow the DMS100TM to release resources for redundant PRI trunks in a call. Example: A is a PSTN subscriber. A calls B. B is a subscriber on the CPE connected to the PSTN by a PRI. B transfers or forwards the call to C. C is another PSTN subscriber. This sets up 2 PRI trunks (B-channels), one incoming and one outgoing. When the transfer is completed, this feature will allow the two B-channels to be released and the DMS serving this PRI group will link the two calls together through its own internal network.

The DMS100TM only supports the network side of this service, the PBX or CPE must implement the user side RLT protocol for proper performance.

This optional feature is only available on software loads NA007 and higher.

This service is specified in Section 5 of NIS A211-1, Release 7.05.

APPENDIX A - Glossary

B8ZS:	Bipolar with 8-Zero Substitution
BFCV:	Binary Facility Coding Value
CND:	Calling Number Delivery
CPN:	Calling Party Number
CRC:	Cyclical Redundancy Check
ESF:	Extended Superframe Format
FDL:	Facility Data Link
FX:	Foreign Exchange
INWATS:	Inward Wide Area Telephone Service
ISA:	Integrated Services Access
ISDN:	Integrated Services Digital Network
kbps:	kilobits per second
MF:	Multi-frequency
NIS:	Network Interface Specification
NPI:	Numbering Plan Identification
OUTWATS:	Outward Wire Area Telephone Service
PBX:	Private Branch Exchange
PRI:	Primary Rate Interface
PSTN:	Public Switched Telephone Network
RLT:	Release Link Trunk
SIJ:	Service Interface Jack
TIE:	Tie trunk